

# LED Undercabinet Light Fixture

## UC-LED-S12/18/24/26/48




Powered by **CREE** LEDs<sup>™</sup>



UC-LED-S48




UC-LED-S36



UC-LED-S12




UC-LED-S24



UC-LED-S18




UC-LED-S18



UC-LED-S24



UC-LED-S12



UC-LED-S36



UC-LED-S48

### FEATURES

- \* Consisting of an extruded aluminum alloy body
- \* Architectural white UV resistant powder coat finish
- \* Input voltage: 120V AC
- \* Highest quality long life CREE MX-SERIES LEDs
- \* Low Tj for long life, low lumen depreciation
- \* IC current controlled LED circuits
- \* Low starting temp -20OC
- \* ON / OFF switch
- \* Color temperature — 3000K ( other K value optional)

### SPECIFICATION

Model No.	S12	S18	S24	S36	S48
LED Qty	3 pcs	5 pcs	7 pcs	10 pcs	14 pcs
Wattage	5 W	8 W	11 W	14 W	18 W
Mean Lumens	240 lm	389 lm	522 lm	778 lm	1044 lm
Output Current	346 mA	344 mA	321 mA	346 mA	344 mA
Linkable	Connect up to 20 in fixtures or 100W max				

\* Different LED Kelvin temperature available with 4-6 week lead time. Please call for a quote.

\*\* DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.