



LED-365-NF



Product Description:

Heavy-duty die-cast construction with modular LED light engine design. This slim-profile luminaire can be perfectly used in parking garage, canopy, or high ceilings. It provides an easy installation with quick mount structure for contractors to work safely and easily in the confined-space areas.

Optional mounting and Kelvin color* with adder.

Features:

LISTING

UL and CUL listed for wet locations

HOUSING

Solid construction die-cast aluminum body

UV stabilized power coated finish

LENS

Unique quick mount design

OPTIONS

Optional photocell with adder


Motion sensor capability

Finish - White

Optional 347V with adder




Available Options




Quick mount

Line Drawing

Dimensions





Specification			
Model No.	LED-365-L20-NF	LED-365-L40-NF	LED-365-L60-NF
System watts	55	105	156
Lumen Output	5700 lm**	13308 lm**	15285 lm**
Color	5000 K		
MA •	700 MA		
Input Voltage	120~277V		
CRI •	70+		
Starting Temp	-40°C		
Equivalent	150W MH	250W MH	400W MH

- Different LED Kelvin temperature available with 4-6 week lead time. Please call for a quote.
- ** DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.





