



LED Surface Mount Light

LED-326-C



Product Description:

This architectural LED luminaire is suitable for many environments. It can be wall-mounted, pendant-mounted, and canopy-mounted. It can be used for indoor purposes as well as outdoor environments. Utilizing patented heat sink design to lower Tj temperature, this luminaire can last for a very long time with very little lumen depreciation. With various optics available, this product is a lighting designer's perfect companion!

Optional mounting and Kelvin color* with adder.

Features:

LISTING

UL and CUL listed for wet locations

HOUSING

Solid construction die-cast aluminum body

FINISH

UV stabilized powder coated finish


LENS

25 degree optic lenses available with adder

OPTIONS


Finish - Gray. Color option with adder

Available Options




25° Optics available

Line Drawing



Dimensions



Specification

Model No.	LED-326-C	LED-326-CS
System watts	13	
Lumen Output	1394.15 lm**	
Color	5000 K	
MA	300 MA	
Input Voltage	120~277V	
CRI	70+	
Starting Temp	-40°C	
Equivalent	70W-100W MH	

* Different LED Kelvin temperature available with 4-6 week lead time. Please call for a quote.

** DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.