



LED Surface Mount Light

VTL-955S/956S/957S



Line Drawing

Dimensions

Product Description:

This rugged vapor-proof LED light is built to last. With industrial-grade rubber gaskets and automobile grade aluminum, this LED light is a beacon against Mother Nature. With a COB LED inside, it provides performance lighting while utilizing very little power. With a die-cast guard on the outside of the glass. It protects the high power LED. This fixture can be used in warehouse, docks, restaurants, or any outdoor application.

Optional mounting and Kelvin color* with adder.

Features:

LISTING

UL and CUL listed for wet locations


HOUSING

Solid construction die-cast aluminum body ½" conduit plug-all 4 sides

FINISH

UV stabilized powder coated finish Finish - Sandblasted Silver

Specification			
Model No.	VTL-955S	VTL-956S	VTL-957S
System watts	11		
Lumen Output	884lm**		
Color	5000K		
MA			
Input Voltage	120V		
CRI	70+		
Starting Temp	40°C		
Equivalent •	100W Incandescent		



9.625" (244mm)

> 5.375" (137mm)

> > 9.06"

** DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.





9.625" (244mm)

7.125" (181mm)