

SML-023




Available Options




Quick mount

Line Drawing



Dimensions





Product Description:

This canopy light has a slim and low profile design which provides safe and a visually appealing lighting experience. Luminaire can be mounted directly to the ceiling with 3/4" pendant mounting option available. Quick mount structure for contractors to work safely and easily in the confined-space areas. It is a perfect solution to replace 200 metal halide lamp with a benefit of low maintenance cost.

Optional mounting and Kelvin color* with adder.

Features:

LISTING

UL and CUL listed for wet locations

HOUSING

Die-cast aluminum body

FINISH

UV stabilized powder coated finish

LENS

Prismatic lens for uniform light distribution

OPTIONS

Easy installation

Finish - White. Color option with adder

Specification		
Model No.	•	SML-023
System watts)	68
Lumen Output	•	6429 lm**
Color	•	5000K
MA	•	830 MA
Input Voltage)	120~277V
CRI	•	70+
Starting Temp	>	-40°C
Equivalent	•	200W MH

^{*} Different LED Kelvin temperature available with 4-6 week lead time. Please call for a quote.

^{**} DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture.

Actual production units may vary from the values reported here by up to ±10%.





